

Our Ref.: 3842-8

U.S. PATENT APPLICATION

Inventor: Leif Einar AUNE

Invention: COMMUNICATION IDENTIFIER METHOD

*NIXON & VANDERHYE P.C.
ATTORNEYS AT LAW
1100 NORTH GLEBE ROAD
8TH FLOOR
ARLINGTON, VIRGINIA 22201-4714
(703) 816-4000
Facsimile (703) 816-4100*

SPECIFICATION

sub a1 → ~~Communication Identifier Method~~

sub a2
Field of the invention

The invention is related to RADIUS-accounting communication and in particular [an arrangement] a method for assigning-unique identifiers for allowing communication between a GPRS (General Packet Radio Service)-system and a RADIUS (Remote Authentication Dial In User Service) server.

sub a3
The problem areas

sub a4
RADIUS (Remote Authentication Dial In User Service) is a protocol used to authenticate remote users logging in to a network and is used as the way to authenticate users in a GPRS-system. In case the RADIUS-server provides the subscriber with a dynamic IP-address to use, a RADIUS accounting-server is used to mark the address as used and freed.

sub a5
The GPRS (General Packet Radio Service) offers a high-speed, packet-switched, mobile datacommunication network, where the subscribers can connect themselves to an external network from a mobile terminal. The GPRS system consists mainly of two nodes, where the Gateway GPRS Support Node (GGSN) is the component involved in this invention.

sub a6
The subscribers need an IP (Internet Protocol)-address to route packets to and from the external network. This address can be provided by a RADIUS-server, in which case a unique identifier must be provided to relate the subscriber to this IP-address. The identifier is described as attribute Acct-Session-Id in IETF RFC 2139 (April 1997) "RADIUS Accounting". Due to the nature of a GPRS system, a subscriber will with a high degree of probability be connected to an external network for a long time, allocating the IP-address for an equally long period of time.

sub a7
The RADIUS accounting server is requested to start an accounting session when the RADIUS client sends an accounting start request towards the RADIUS accounting server. This is done to mark the address as used by the subscriber in the RADIUS accounting server. The RADIUS client in the accounting start request must give an identifier, and the same identifier is sent in an accounting stop request to stop the accounting and release the IP-address. The identifier must be generated for each

A1

subscriber' connection receiving an address from the RADIUS server, and it must be guaranteed to be unique for each connection.

Sub A15

The GPRS-system can be connected to several external networks, and all the networks may use the same RADIUS server. The different networks may also contain the same range of addresses (private address-space), and hence the RADIUS server must be able to give out the same IP-address to subscribers belonging to the different external networks.

10

~~Known solutions and problems with these.~~

Sub A19

The identifier is usually made from the time in the system acting as a client (usually an NAS) towards the RADIUS server. Other solutions are one or several counters that are incremented for each new accounting session and/or for each restart of the system. It is also known that some implementations use process identifiers as a part of the identifier.

15

Sub A10

The main problem with the above-mentioned solutions is that they all require system resources to create and maintain the generation of the identifiers. Getting the system-time does not require any storage, but may be inaccurate or inefficient in case of a large number of simultaneously requests for the system-time. Having counters to be incremented will use system memory, computational time to recalculate the values and some algorithm to avoid two subscribers getting the same value of the counter. The counter must also be large enough to generate enough identifiers to all the possible subscribers. These values will not be predictable and are usually based on statistical distribution to assure uniqueness; hence they can not be guaranteed to be absolutely unique.

20

25

~~Objects of the invention~~

Sub A11

An object of the invention is to overcome the problems related to prior art solutions in the art, by providing unique identifiers without involving necessity for any new system resources other than those already available.

30

Sub A12

~~Brief disclosure of the invention~~

The method according to the invention includes the steps of:

- connecting one or more external networks to the GPRS system and identifying the or each network with an APN (Access Point Name), and
 - assigning to an or each APN external network a gateway address, and the further steps of:
- 5
- passing an APN-external network authentication request from a GGSN (Gateway GPRS support Node) to said RADIUS server,
 - providing from said RADIUS server to said GGSN upon such request a subscriber IP (Internet Protocol) address to be stored in said GGSN (Gateway GPRS Support Node), said subscriber IP address being unique for the respective APN external network
- 10
- using said GGSN for combining the APN gateway address and the subscriber IP address, to form a unique subscriber identifier, and
 - sending from said GGSN said identifier to the RADIUS server for accounting, e.g. in the form of an ASCII string.

15 Further characteristic features of the invention will appear from the following description and the attached patent claims, and with reference to the enclosed drawing figures.

20 **Brief description of the drawings**

sub a(13) Figure 1 illustrates the basic steps for generating an identifier, and

Figure 2 illustrates three external networks with a subscriber connected to each network.

25 ~~Detailed description of embodiments~~

sub a(14) The invention is now to be described firstly with reference to Figure 1.

sub a(15) 30 When connecting an external network to the GPRS system, the network is identified with an Access Point Name (APN), such as e.g. APN1 (see Figure 1). Each APN is given a gateway address GW in the GGSN, as seen from the external network. By assuring that this IP-address is unique for each APN defined in the GGSN, all the external networks will have its own, unique identifier. Since two subscribers (MS) in

35 the same external network should never use the same IP-address at the same time, subscribers connected to the same APN will always have different IP-addresses. The

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

A15 idea is to combine these two IP-addresses, the gateway-address for the APN and the address assigned to the subscriber, to form the identifier.

Sub Cent When the GGSN receives an IP-address to send to the subscriber from the RADIUS-server, it looks up the gateway-address belonging to the external net to which the subscriber is connecting himself. This address has already been configured when the external network is attached to the GPRS-system, and checked to be unique within the GGSN.

Sub Cent
10 To construct the identifier to send to the RADIUS accounting-server the GGSN will now use these two available IP-addresses. The addresses can be appended to form a eight byte long identifier (in case of IP-addresses from IP version 4), or the numbers could be converted to ASCII numbers to make the string printable. When the numbers are converted it would be wise to insert dots (ASCII value 46) between the decimal-
15 groups in the addresses to be able to clearly see the addresses used in the identifier (e.g. for an operator looking into the accounting records).

Sub Cent
Gateway-address = 129.24.24.1

20 MS IP-address = 129.24.24.24

ASCII codes: 129 24 24 1 129 24 24 24 (non printable)

Or transform the number to ASCII codes for the numbers to make them printable:

25 ASCII codes: 49 50 57 46 50 52 46 50 52 46 49 46 49 50 57 46 50 52 46 50 52 46 50 52
(which would be readable as "129.24.24.1.129.24.24.24")

30 The identifier is suitably passed to the RADIUS server as an ASCII string. (See Figure 1).

Thus, the gateway address is the address of the GPRS-system/GGSN as seen from the external network (APN, e.g. APN1) and the subscriber could be a mobile terminal MS connected to the external network through the GPRS-system.

TELECOM

On Figure 2, the subscribers MS1, MS2 and MS3 have for sake of reference to their respective networks APN1, APN2 and APN3 been indicated on the right hand side of the drawing figure.

- 5 The APN name and the respective APN gateway address to the GGSN seen from the network are configured, as such new network is linked to the GPRS system. The operator will normally manually assign the APN name and the gateway address, and the RADIUS server is not involved in such operation.

Figure 2 shows three external networks connected to a GGSN node in a GPRS system. Each network has one subscriber connected and all the three networks use the same RADIUS server for authentication and dynamic IP-address allocation for the subscribers. Even though the networks identified as APN2 and APN3 has assigned the same IP-address to the two subscribers, the identifier will be unique because of the

15 different gateway addresses. Table I shows the generated identifiers for the three subscribers.

Table 1

APN	Gateway Address	Subscriber IP Address	Identifier
APN1	129.24.24.1	129.24.24.24	"129.24.24.1.129.24.24.24"
APN2	193.25.01	193.25.5.1	"193.25.0.1.193.25.5.1"
APN3	193.26.0.1	193.25.5.1	"193.26.0.1.193.25.5.1"

20 **Advantages**

The creation of the identifier used for accounting purposes described above will not involve any new resources than the ones already available. Since the addresses already are unique, the combination of the two addresses will form a perfectly valid identifier. This will not restrict any limitations on concurrency regarding RADIUS accounting

25 messages, and the identifier is guaranteed unique as long as the subscriber is still using the assigned IP-address (i.e. no accounting stop has been sent towards the RADIUS server). The creation of the identifier will not use any extra resources whatsoever, and will always be available as long as an IP-address exists.

30 The identifier will also be very predictable, and only by looking at this one can tell which external network the accounting record belongs to, as well as knowing the IP-address for the subscriber.

TELECOM

Sub 90

Sub 90

Sub 90

